

# STARPOWER

SEMICONDUCTOR

**IGBT**

## GD400CLX65C2S

**650V/400A chopper in one-package**

### General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as inductive heating.


### Features

- Low  $V_{CE(sat)}$  Trench IGBT technology
- 6 $\mu$ s short circuit capability
- $V_{CE(sat)}$  with positive temperature coefficient
- Maximum junction temperature 175°C
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

### Typical Applications

- Switching mode power supply
- Inductive heating
- Electronic welder

### Equivalent Circuit Schematic



**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
$V_{CES}$	Collector-Emitter Voltage	650	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	485	A
	@ $T_C=60^{\circ}\text{C}$	400	
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	800	A
$P_D$	Maximum Power Dissipation @ $T_{vj}=175^{\circ}\text{C}$	1190	W

**Diode**

Symbol	Description	Values	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	650	V
$I_F$	Diode Continuous Forward Current	400	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	800	A

**Module**

Symbol	Description	Values	Unit
$T_{vjmax}$	Maximum Junction Temperature	175	$^{\circ}\text{C}$
$T_{vjop}$	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}$ , $t=1\text{min}$	2500	V

**IGBT Characteristics**  $T_c=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=25^\circ\text{C}$		1.45	1.90	V	
		$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=125^\circ\text{C}$		1.60			
		$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}$		1.70			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=6.40\text{mA}, V_{CE}=V_{GE}, T_{vj}=25^\circ\text{C}$	5.1	5.8	6.5	V	
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$			1.0	mA	
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_{vj}=25^\circ\text{C}$			400	nA	
$R_{Gint}$	Internal Gate Resistance			1.0		$\Omega$	
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		46.4		nF	
$C_{res}$	Reverse Transfer Capacitance				0.91		nF
$Q_G$	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		2.77		$\mu\text{C}$	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=300\text{V}, I_C=400\text{A}, R_G=1.8\Omega, L_S=43\text{nH}, V_{GE}=\pm 15\text{V}, T_{vj}=25^\circ\text{C}$		243		ns	
$t_r$	Rise Time			70		ns	
$t_{d(off)}$	Turn-Off Delay Time			272		ns	
$t_f$	Fall Time			65		ns	
$E_{on}$	Turn-On Switching Loss				3.2		mJ
$E_{off}$	Turn-Off Switching Loss				8.3		mJ
$t_{d(on)}$	Turn-On Delay Time				251		ns
$t_r$	Rise Time				76		ns
$t_{d(off)}$	Turn-Off Delay Time				292		ns
$t_f$	Fall Time				79		ns
$E_{on}$	Turn-On Switching Loss	$V_{GE}=\pm 15\text{V}, T_{vj}=125^\circ\text{C}$		5.7		mJ	
$E_{off}$	Turn-Off Switching Loss			9.8		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=300\text{V}, I_C=400\text{A}, R_G=1.8\Omega, L_S=43\text{nH}, V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$		253		ns	
$t_r$	Rise Time			77		ns	
$t_{d(off)}$	Turn-Off Delay Time			294		ns	
$t_f$	Fall Time			84		ns	
$E_{on}$	Turn-On Switching Loss				6.3		mJ
$E_{off}$	Turn-Off Switching Loss				10.5		mJ
$I_{SC}$	SC Data		$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}, V_{CC}=300\text{V}, V_{CEM} \leq 650\text{V}$		2000		A

**Diode Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$		1.55	2.00	V
		$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=125^\circ\text{C}$		1.50		
		$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$		1.45		
$Q_r$	Recovered Charge	$V_R=300\text{V}, I_F=400\text{A},$ $-di/dt=5335\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=43\text{nH}, T_{vj}=25^\circ\text{C}$		11.9		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			191		A
$E_{rec}$	Reverse Recovery Energy			2.76		mJ
$Q_r$	Recovered Charge	$V_R=300\text{V}, I_F=400\text{A},$ $-di/dt=4809\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=43\text{nH}, T_{vj}=125^\circ\text{C}$		19.7		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			217		A
$E_{rec}$	Reverse Recovery Energy			4.35		mJ
$Q_r$	Recovered Charge	$V_R=300\text{V}, I_F=400\text{A},$ $-di/dt=4734\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=43\text{nH}, T_{vj}=150^\circ\text{C}$		21.5		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			225		A
$E_{rec}$	Reverse Recovery Energy			4.70		mJ

**Module Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$L_{CE}$	Stray Inductance			20	nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.35		m $\Omega$
$R_{thJC}$	Junction-to-Case (per IGBT)			0.126	K/W
	Junction-to-Case (per Diode)			0.204	
$R_{thCH}$	Case-to-Heatsink (per IGBT)		0.022		K/W
	Case-to-Heatsink (per Diode)		0.036		
	Case-to-Heatsink (per Module)		0.010		
M	Terminal Connection Torque, Screw M6	2.5		5.0	N.m
	Mounting Torque, Screw M6	3.0		5.0	
G	Weight of Module		300		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs.  $I_C$




Fig 4. IGBT Switching Loss vs.  $R_G$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$




Fig 10. Diode Transient Thermal Impedance





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.